

Basinol TRUCK LONGLIFE 1540 PLUS

80000330

SHPD multigrade motor oil for petrol and diesel engines

Basinol TRUCK LONGLIFE 1540 PLUS is a mineral oil-based high-performance universal motor oil for the year-round supply of mixed vehicle fleets. A uniform engine oil for all vehicles eliminates mix-ups and guarantees economical storage.

Basinol TRUCK LONGLIFE 1540 PLUS is a powerful universal engine oil for extended oil change intervals.

The range of services covers both the requirements of commercial vehicle and passenger car diesel engines and those of gasoline engines.

The high requirements of modern, low-consumption engines to meet the stricter emissions standards (Euro III) are met with reserve.

Technical Data

SAE-Class	15W-40	SAE J 300
Viscosity at + 40 °C	101,40 mm²/s	DIN 51562
Viscosity at + 100 °C	14,50 mm²/s	DIN 51562
Viscosityindex	148	DIN ISO 2909
Density at + 15 °C	0,870 g/cm³	DIN 51757
Pour point	- 33 °C	DIN ISO 3016
Flash point	> +200 °C	DIN ISO 2592
Base Number BN	9,0 mg KOH/g	DIN ISO 3771

(The physical data are average values)

Classifications

- ACEA A3
- ACEA B3
- ACEA E7
- API CI-4
- API SL

Standard application

Caterpillar ECF-1a
 Caterpillar ECF-2
 Cummins CES 20071
 Cummins CES 20072
 Cummins CES 20076
 Cummins CES 20077
 DEUTZ DQC III-10

John Deere JDQ 78 A
 Mack EO-N
 Mack EO-N Premium Plus 03
 MAN M 3275-1 (obsolet)
 Mercedes-Benz: MB 228.3
 Mercedes-Benz: MB 229.1
 MTU DDC BR 2000

MTU DDC BR 4000
 MTU Ölkategorie 2
 Renault RLD
 Renault RLD/RLD-2
 Scania LDF
 Volvo VDS-3 (STD 417-0002)
 ZF TE-ML 07C